

F/UTP 4Pairs cable-category6A-PVC Sheath

P/N: LG2502-005

Content of the Data Sheet																			
Sheath Printing		TBD																	
Customer No.			Customer Reference				White- Blue /Blue Separator White-Orange /Orange Mylar AL/Mylar Drain wire White-Green /Green White-Brown /Brown Rip-cord Sheath												
Category		F/UTP CAT6A-4P-PVC																	
Reference Standard		ISO/IEC11801、ANSI/TIA-568.2-D																	
Conductor		Material		SOLID-Bare Copper															
		Nom.O.D.(mm)		0.565	up	+0.01													
				down	-0.01														
Insulation 1		Material		PE															
		Diameter		1.10±0.08mm															
Insulation 2		Material		PE															
		Diameter		1.20±0.08 mm															
Screening Material		Mylar+ AL/Mylar																	
Sheath		Thickness		0.55±0.05mm			Technical Performance (100m) :												
		External O.D.		7.4±0.4 mm			Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	PHASE DELAY ≤ns								
		Surface		Clean, Frap, Satiation			1	20.0	—	74.3	570.0								
		Material		PVC(complies RoHS)			4.0	23.0	3.8	65.3	552.0								
		Color		TBD			8.0	24.5	5.3	60.8	546.7								
Surface Printing		Letter height		3.0±0.3mm			10.0	25.0	5.9	59.3	545.4								
		Color		Black			16.0	25.0	7.5	56.2	543.0								
		Print error & Space		≤±0.5%, 1m			20.0	25.0	8.4	54.8	542.1								
Core Color		1 White- Blue /Blue		2 White-Orange /Orange			25.0	24.3	9.4	53.3	541.2								
		3 White- Green /Green		4 White- Brown /Brown			31.25	23.6	10.5	51.9	540.4								
Packing		Drum					62.5	21.5	15.0	47.4	538.6								
Wooden Tray dimension		According to the requires					100	20.1	19.1	44.3	537.6								
Packing length		(305±1.5)m					200	18.0	27.6	39.8	536.5								
Rip-cord		Yes		Drain wire		Yes		250	17.3	31.1	38.3	536.3							
Sheath Physical Properties		Before Aging Tensile Strength (Mpa)		≥13.5				300	16.8	34.3	37.1	536.1							
		Elongation (%)		≥150				500	15.2	45.3	33.8	535.6							
		Aging Period (°C×hrs)		100°C×24h×7d				Frequency PSNEXT ELFEXT PSELFEXT											
		After Aging Tensile Strength (Mpa)		≥12.5				(MHz)	≥dB	≥dB	≥dB								
		Elongation (%)		≥125				1	72.3	68.0	65.0								
Electrical Characteristics (20°C)		Cold bend (-20±2°C×4h) 8×Cable O.D., No visible cracks						4	63.3	56.0	53.0								
		Impedance(Ω) 1.0-250.0MHz		100±15				8	58.8	49.9	46.9								
		250.0-500.0MHz		100±22				10	57.3	48.0	45.0								
		1.0-500.0MHz Delay Skew (ns/100m)		≤45				16	54.2	43.9	40.9								
		Unbalanced-to-ground capacitance (pf/100m) max		330				20	52.8	42.0	39.0								
		DC Resistance (Ω/100m) max		9.38				25	51.3	40.0	37.0								
		DC Conductor Resistance Unbalance (%) max		5.0				31.25	49.9	38.1	35.1								
								62.5	45.4	32.1	29.1								
								100	42.3	28.0	25.0								
								200	37.8	22.0	19.0								
								250	36.3	20.0	17.0								
Version		A/03		Date		2024-01-09		Revised By		Caihangle		Audited By		Nidonghua		Approved By		Nidonghua	

Number	Revise Contents	Revise Reasons	Revised By	Audited By	Approved By	Date
A/02	Specification Version 2		Caihanglie	Nidonghua	Nidonghua	2021-04-25
A/03	Specification Version 3		Caihanglie	Nidonghua	Nidonghua	2024-01-09